

X1600 Socket

The Cato X1600 Socket is a high performance SD-WAN device that enables optimized and secure enterprise WAN, Internet, and cloud connectivity.



Specification

Max Tunnel Throughput	1 Gbps
CPU	Intel® Atom® CPU C3558 (4 cores)
System Memory	4GB
Ethernet Port	4 x RJ45 (up to 2.5GbE) ports 2 x 10G SFP+ ports 2 x 1GbE Combo ports (RJ45/SFP) 2 x USB3.0
Storage Device	16GB eMMC SSD
Serial Port	RJ45 and micro-USB (auto-detect)
LEDS	2 x multicolor LEDs, GPIO-controlled
Power Input	+12V DC Locking Barrel Jack
Power Adapter (PSU)	External 60W PSU Regional AC cord
Dimension	D: 256mm x W: 200mm x H: 44mm D: 10.1in x W: 7.9in x H: 1.7in
Operating Environment	0 to +40 C° operating temperature (including external PSU) 10 to 95% humidity non-condensing
Storage Environment	-30 to +85 C° operating temperature (including external PSU) 10 to 95% humidity non-condensing
Certifications	FCC/CE/CB/UL
Mounting Options	Desktop Wall-mount accessory kit (priced separately) Rackmount accessory kit (priced separately)
Weight	2.8KG packed in box 1.28KG unpacked