

X1600 Socket

The Cato X1600 Socket is a high performance SD-WAN device that enables optimized and secure enterprise WAN, Internet and cloud connectivity.



Specification

Max Tunnel Throughput	1 Gbps
CPU	Intel® Atom® CPU C3558 (4 cores)
System Memory	4GB
Ethernet Port	<ul style="list-style-type: none"> 4 ports x 2.5GbE RJ45 Ports 2 ports x 10G SFP+ Ports 2 ports x 1GbE Combo Ports (RJ45/SFP) 2 ports x USB3.0
Storage Device	16 GB eMMC SSD
Serial Port	Cisco RJ-45 and micro-USB (auto-detect)
LEDS	2 x multicolor LEDs, GPIO-controlled
Power Input	+12V DC Locking Barrel Jack
Power Adapter (PSU)	<ul style="list-style-type: none"> External 60W PSU Regional AC cord
Dimension	<ul style="list-style-type: none"> 256 x 200 x 44mm (LxWxH) 10.0 x 7.9 x 1.7in. (LxWxH)
Operating Environment	<ul style="list-style-type: none"> 0 to +40 C operating temperature (including external PSU) 10 to 95% humidity non-condensing
Storage Environment	<ul style="list-style-type: none"> -30 to +85 C operating temperature (including external PSU) 10 to 95% humidity non-condensing
Certifications	FCC CE CB UL
Mounting Options	<ul style="list-style-type: none"> Desktop Wall-mount accessory kit (priced separately) Rackmount accessory kit (priced separately)
Weight	<ul style="list-style-type: none"> 2.8KG packed in box 1.28KG unpacked